

## Toisa Coral

### Type AP416 - ROV Support and Platform Supply Vessel

#### OUTLINE SPECIFICATION / DATA SHEET



#### GENERAL

Builder / year	Applodore, UK / 1999
Flag / POR	British/London
Class	Lloyds Register of Shipping + 100A1, Offshore Supply Vessel, IWS, + LMC, UMS, DP(AA).with Intact & Damage Stability according to IMO Resolution A.469 (XII)
Gross tonnage	2,401
Nett tonnage	966
Deadweight (summer)	3,248 tonnes

#### DIMENSIONS

Length OA	73.80 m
Breadth mid.	16.00 m
Draught (summer)	6.30 m

#### SPEED

Service speed	abt. 10-12 knots
---------------	------------------

#### CARGO DECK

Sheathed deck area	50.0 m x 13.5 m = 675m <sup>2</sup>
Deck strength	5 tonnes / m <sup>2</sup>
Deck load	1,500 tonnes

#### CARGO CAPACITIES

	Approx. at 100%
Fuel oil cargo	1,007 m <sup>3</sup>
Potable water	768 m <sup>3</sup>
Drill water	681 m <sup>3</sup>
Dry bulk @ 80 psi.	4 x 51.0 m <sup>3</sup> = 204 m <sup>3</sup> (7,204 ft <sup>3</sup> )
Liquid mud @ 2.8 sg	395 m <sup>3</sup> - (2,484 bbls)
Brine @ 2.8 sg	425 m <sup>3</sup> - (2,673 bbls)
Base oil	169 m <sup>3</sup> - (1,062 bbls)

#### CARGO PUMPING

Fuel oil cargo	1 x 200 m <sup>3</sup> /hr @ 9 bar
Potable water	1 x 150 m <sup>3</sup> /hr @ 9 bar
Drill water	1 x 150 m <sup>3</sup> /hr @ 9 bar
Dry bulk compressors	2 x 30 m <sup>3</sup> /m @ 80 psi
Liquid mud	2 x 75 m <sup>3</sup> /hr @ 21 bar
Brine	1 x 75 m <sup>3</sup> /hr @ 21 bar
Base oil	1 x 100 m <sup>3</sup> /hr @ 9 bar

#### DP2 SYSTEM

DP / Joystick Control	IMO Class 2 DP System - Kongsberg K-Pos DP-21
Reference Systems	2 x Seatex DGPS HiPAP
Transponder Deployment Joystick Control	"A" Frame + 3,000 m Winch Simrad SJS11

#### PROPULSION

Two Wärtsilä 6L26 marine diesel engines each developing 2,614 BHP @ 1,000 rpm each driving 1,500 kW shaft alternator and CP propeller	
Total developed power	3,900 kW (5,228 BHP)

#### GENERATORS

Shaft alternator	440 / 3 / 60
Main alternators	2 x 1,500 kW
Emergency alternator	2 x 276 kW
	1 x 160 kW

#### THRUSTERS

Forward tunnels	2 x 590 kW
Aft tunnels	2 x 590 kW

#### DECK MACHINERY

Deck/stores crane	6 tonnes double fall, with 3 tonne winch 6 tonnes @ 7 m radius 3 tonnes @ 12 m radius 2.65 tonnes @ 13.6 m radius
Windlass (Split P & S)	2 x 22t hyd.
Tugger Winches	2 x 10t hyd.
Capstans	2 x 10t hyd.

#### ACCOMMODATION

Wheelhouse and accommodation fully air conditioned	
Single berth cabins	2 suites + 5 en-suite
Two berth cabins	16 cabins
Hospital	1 berth
Complement	40 persons

#### STABILISATION

Two passive roll reduction stabilisation tanks
--

#### Sealion Shipping Limited

Gostrey House, Union Road, Farnham, Surrey GU9 7PT

Tel: +44 (0)1252 737773 Fax: +44 (0)1252 737770 Email: [info@sealionshipping.co.uk](mailto:info@sealionshipping.co.uk) [www.sealionshipping.co.uk](http://www.sealionshipping.co.uk)

The particulars are believed to be correct, but are not guaranteed. (Please seek confirmation of current accuracy before relying on same)